


GEKKO magnetic anti-slip layer

Easily applied and removed



- ▶ Ideal protection for loads
- ▶ Easily applied and removed within a few seconds
- ▶ Magnetic adhesion on the forks
- ▶ Higher occupational safety: minimized risk of slipping loads
- ▶ Reduction of damages and protection of sensitive surfaces
- ▶ Less vibrations
- ▶ Noise reduction, especially when transporting metal components
- ▶ Abrasion and cut resistance for a long operating life
- ▶ Also suitable for pallet trucks
- ▶ Easy attachment on the lift truck (i.e. on the mast) when not in use
- ▶ For temporary use



Molded magnets at the underside of GEKKO



Attach to the lift truck when not in use



With bracket for an easy take off



Also applicable as impact protection at the forklift chassis



Flexible length adjustment:
Just continue the protruding length in the fork back!



The illustrations only represent the basic principles and do not constitute a contractual entitlement.

GEKKO magnetic anti-slip layer: type list

Item ID	Description	GEKKO width (inch)	GEKKO length (inch)	For fork width (inch)	for fork length (inch)*	Technical Characteristica
GEKKO75x0750	GEKKO Magnetic anti-slip layer	3	30	3.15	32	approx. 0.43" anti-slip surface (+/- 0.06") Shore hardness DIN 53505: 75+/- 5 Shore A Operating temperature: -40°F to +176°F Rebound resilience DIN 53512: 35% Magnetic holding force: 1,2 N /cm ² Qualified for temporary use
GEKKO75x0950			37		40	
GEKKO75x1150			45		36 / 48	
GEKKO75x1350			53		40 / 42 / 48	
GEKKO75x1550			61		48 / 54	
GEKKO75x1750			69		60 / 72	
GEKKO75x1950			77		60	
GEKKO75x2350			93		84 / 96	
GEKKO95x0750		3.75	30	4	32	
GEKKO95x0950			37		40	
GEKKO95x1150			45		36 / 48	
GEKKO95x1350			53		40 / 42 / 48	
GEKKO95x1550			61		48 / 54	
GEKKO95x1750			69		60 / 72	
GEKKO95x1950			77		60	
GEKKO95x2350			93		84 / 96	
GEKKO115x0750		4.5	30	4.75 5 5.25	32	
GEKKO115x0950			37		40	
GEKKO115x1150			45		36 / 48	
GEKKO115x1350			53		40 / 42 / 48	
GEKKO115x1550			61		48 / 54	
GEKKO115x1750			69		60 / 72	
GEKKO115x1950			77		60	
GEKKO115x2350			93		84 / 96	
GEKKO135x0750		5.3	30	5.5	32	
GEKKO135x0950			37		40	
GEKKO135x1150			45		36 / 48	
GEKKO135x1350			53		40 / 42 / 48	
GEKKO135x1550			61		48 / 54	
GEKKO135x1750			69		60 / 72	
GEKKO135x1950			77		60	
GEKKO135x2350			93		84 / 96	

The illustrations only represent the basic principles and do not constitute a contractual entitlement.

GEKKO magnetic anti-slip layer: type list

Item ID	Description	GEKKO width (inch)	GEKKO length (inch)	For fork width (inch)	for fork length (inch)*	Technical Characteristica
GEKKO145x0750	GEKKO Magnetic anti-slip layer	5.7	30	6	32	approx. 0.43" anti-slip surface (+/- 0.06")
GEKKO145x0950			37		40	
GEKKO145x1150			45		36 / 48	
GEKKO145x1350			53		40 / 42 / 48	
GEKKO145x1550			61		48 / 54	
GEKKO145x1750			69		60 / 72	
GEKKO145x1950			77		60	
GEKKO145x2350			93		84 / 96	
GEKKO175x0750		6.9	30	7	32	Shore hardness DIN 53505: 75+/- 5 Shore A
GEKKO175x0950			37		40	
GEKKO175x1150			45		36 / 48	
GEKKO175x1350			53		40 / 42 / 48	
GEKKO175x1550			61		48 / 54	
GEKKO175x1750			69		60 / 72	
GEKKO175x1950			77		60	
GEKKO175x2350			93		84 / 96	
GEKKO195x0750		7.7	30	8	32	Operating temperature: -40°F to +176°F
GEKKO195x0950			37		40	
GEKKO195x1150			45		36 / 48	
GEKKO195x1350			53		40 / 42 / 48	
GEKKO195x1550			61		48 / 54	
GEKKO195x1750			69		60 / 72	
GEKKO195x1950			77		60	
GEKKO195x2350			93		84 / 96	
GEKKO245x2350		9.7	93	10	84 / 96	Rebound resilience DIN 53512: 35%
						Magnetic holding force: 1,2 N /cm ²
						Qualified for temporary use

* Please select a GEKKO length that is either minimum 2.00" shorter or 6.00" longer than the nominal length of the fork

PLEASE OBSERVE: Do not shorten GEKKO magnetic anti-slip layers, continue the protruding length in the fork back.

The illustrations only represent the basic principles and do not constitute a contractual entitlement.